

Australian Made Rural Water Tanks

ZINCALUME® and COLORBOND® 26,000L-365,000L

Build your 3D tank online.





1800 632 410





Rural Corrugated and Streamline steel tanks

Kingspan tanks range are built tough in genuine BlueScope Steel to suit the harsh Australian conditions. Available in ZINCALUME® or in the full range of genuine COLORBOND® colours, all tanks come with a unique 7 layer liner making them ideal for rural applications. Tanks are Australian made and come with a 20 year conditional warranty.

Tank sizes



Kingspan Rhino Corrugated tanks range from 26,000L - 365,000L.

Model	Capacity for 2.2m high tanks*		Tank	Pad	
	Litres	Gallons	Diameter	Diameter	
RT-25	26,062	5,792	3.88	5.5	
RT-40	40,723	9,049	4.85	6.5	
RT-60	58,640	13,031	5.82	7.5	
RT-80	79,816	17,737	6.79	8.5	
RT-100	104,250	23,167	7.76	9.5	
RT-130	131,941	29,320	8.73	10.5	
RT-160	162,890	36,198	9.71	11.5	
RT-200	197,097	43,799	10.68	12.5	
RT-230	234,562	52,125	11.65	13.5	
RT-275	275,284	61,174	12.62	14.5	
RT-310*	309,235	68,710	11.65m (2.9m h)	13.5	
RT-365*	362,979	80,639	12.62m (2.9m h)	14.5	



NOTE: Sizes listed are gross capacities. Effective capacities vary depending on the size and position of inlets and outlets. *RT-310 and RT-365 are 2.9m high

Standard Inclusions

Aquamark tank liner, full COLORBOND® range¹, BlueScope steel corrugated wall and roof sheets, tank inlet, 50mm outlet and ball valve, removable internal/external ladder, lockable access hatch, 100mm bell mouth overflow, magnesium anodes for corrosion protection, Hiflow Deep Leaf Basket and 20 year conditional warranty.

†not all colours are avaiable in the Heritage range. Contact Kingspan for more information.

Optional Extras

Tank level gauge, dust and vermin proofing seal, additional outlets, inletsand valves, firefighting outlets, 150mm bell mouth overflows, 50mm scour drain, and more!





Tank sizes



Kingspan Heritage Corrugated and Streamline tanks range from 27,000L - 353,000L.



Corrugated profile

Tank code	Litres	Height	Diameter
СТ6	27,396	2.27	3.92
СТ9	39,383	2.27	4.70
CT12	53,735	2.27	5.49
CT15	69,866	2.27	6.26
CT20	88,864	2.27	7.06
CT25	109,584	2.27	7.84
CT30	132,781	2.27	8.63
CT35	157,868	2.27	9.41
CT41	184,761	2.27	10.18
CT48	215,333	2.27	10.99
CT54	246,984	2.27	11.77
CT60	280,804	2.27	12.55
CT70	315,843	2.27	13.31
CT80	353,947	2.27	14.09

Streamline profile

Litres	Height	Diameter
54,682	2.31	5.49
71,097	2.31	6.26
90,430	2.31	7.06
111,515	2.31	7.84
135,121	2.31	8.63
160,650	2.31	9.41
188,017	2.31	10.18
219,128	2.31	10.99
251,336	2.31	11.77
285,752	2.31	12.55
	71,097 90,430 111,515 135,121 160,650 188,017 219,128 251,336	54,682 2.31 71,097 2.31 90,430 2.31 111,515 2.31 135,121 2.31 160,650 2.31 188,017 2.31 219,128 2.31 251,336 2.31

Reinforced high durable Aquamark® liner

Our tank liners are fabricated in our Australian factory and have been for over 20 years.

Our experienced liner fabricators use the latest welding technologies and state of the art machinery to produce liners of the very highest quality.

The Aquamark® Liner features a unique 7 layer construction which offers durability, flexibility and strength.

Once installed, you'll enjoy many years of trouble-free usage.

- Proudly Australian made
- Water potable certified (AS/NZS4020)
- Made to withstand harsh conditions
- Temperature range: -40°C to +70°C
- Polypropylene coating applied for superior resistance to flex cracking
- Chemical and stress crack resistant
- BPA free
- 100% Lead and Phthalate free
- 100% recyclable material





Colour Range



Our tanks come in the full range of genuine Bluescope COLORBOND® colours*.



The colors displayed have been reproduced to represent COLORBOND® colour swatches as accurately as possible. †not all colours are avaiable in the Heritage range. Contact Kingspan for more information.

How many litres of water can you harvest per year?

Use this formula to calculate how much rainwater you can harvest from your roof (catchment area)

Catchment Area		Annual Rainfall		Total Rainwater Harvested	
	m ²	mm		L	
Example: An average 600m can harvest 210		dium sized shed (350m²) in year.	a region w	ith an annual rainfall of	

Kingspan Water & Energy Pty Ltd.

Perth

54 Collopy Road Perth Airport WA 6105

Deniliquin Warehouse/Depot

Lot 22 Wakool Road Deniliquin NSW 2710

Sydney

3 Herbert Place Smithfield NSW 2164

Melbourne

55 Ricky Way Epping VIC 3076

Brisbane

Unit 2/59 Link Drive Yatala QLD 4132

1800 632 410









We take every care to ensure that the information in this document is accurate at the point of publication. Specification may vary (within a small parameter) due to manufacturing process variations or environmental conditions. All images are for illustration purposes only and should not be taken as binding. The actual product may vary, and specification/dimensions/colour/ other attributes may differ.

To ensure you are viewing the most recent and accurate product information, please visit this link: https://www.kingspanwatertanks.com.au/rural-tanks-brochure

®Kingspan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the UK, Ireland and other countries.

Registered Office: Kingspan Water & Energy Pty Limited, 3 Herbert Place, Smithfield, NSW 2164

